7U/ 84 HP Chassis VME64x


VME64x

17 Slot Backplane, 2x 400 W





27.75 40.72 345.75 40.72 27.75 Frontansicht 40.72 Fibrungsschienen b 128 fns 80 rva 17x oben ohne ESD-Clip Fibrungsschienen b 128 fns 80 rva 17x unten eil ESD-Clip



Dimensions W: 482.6 mm

H: 310.4 mm D: 283.1 mm

Key features:

- 7U (6+1) 84 HP VME64x System Chassis with fan tray
- Card rack acc. to IEEE 1101.1, 1101.10/11 and IEC 60297-3-101, -102, -103
- Air flow from bottom to top
- VME64x card rack: cover / bottom plate perforated, executed in aluminium, with IEEE guide rails and ESD clip mounted at the bottom, with 3 DC fans 120 x 120 x 38 mm, 102,4 CFM, 39 dB(A)
- VME64x backplane: 6 U, J1/J0/J2, 17+2 slots, with ADC (Automatic Daisy Chain), with 2x P47 connectors for 6 U CompactPCI power supply units
- 2x CompactPCI power supply unit 400 W, with wide range input 90 264 VAC, (3.3 V / 55 A, 5 V / 55 A, 12 V / 14 A, –12 V / 4 A) with PFC, with P47 connector, incl. 8 HP / 3 U front panel
- Power entry module with switch, fuse and filter on the rear side
- Completely assembled and wired
- Other configurations on request

Order number: LMH0000160



www.hartmann-electronic.com Page 1 of 1