


3U VPX Power & GND 2 Slot BACKPLANE J1 Differential, J2 Universal	VITA 46 VITA 65	


Key Features:

- Our VPX Power & Ground Backplanes - the development tool for VPX systems of your first choice
- Compliant to VITA 46.0 baseline specification
- Compliant to VITA 65 
- 2 Slots VPX, J1 Differential, J2 Universal Pattern
- with RTM for all slots and pins
- M3 studs for power entry
- PCB size 128.50 mm x 50.36 mm x 5.4 mm
- 5 HP from slot to slot (25.40 mm)
- Flexible keying and alignment mechanism
- with geographical address pins
- Reference clock
- Auxiliary clock
- System Reset
- With JTAG connector on first slot (JT1)
- System Management Interface on the backplane (I2CA, I2CB)
- Non-Volatile Memory Read Only signal set by Jumper BR1
- Battery backup option setting by Jumper XBAT. Vbat external or connected to 3.3 VAUX.
- Max. Input current per backplane
VS1:VS2:VS3 = 28A : 28A : 30A
- Operating temperature: -40°C - +85°C
- Storage temperature: -55°C - +85°C
- Flammability rating: UL94-V0
- Custom assembly or modification on request
- Order number: B193200010

Front side



Back side



3U VPX Power & GND 2 Slot BACKPLANE J1 Differential, J2 Universal	VITA 46 VITA 65	
--	----------------------------------	--

2) Pin Assignment

Pin Assignment VPX J0 (Utility Connector)

	Row i	Row h	Row g	Row f	Row e	Row d	Row c	Row b	Row a
1	Vs1	Vs1	Vs1	Vs1	No Pad*	Vs2	Vs2	Vs2	Vs2
2	Vs1	Vs1	Vs1	Vs1	No Pad*	Vs2	Vs2	Vs2	Vs2
3	Vs3	Vs3	Vs3	Vs3	No Pad*	Vs3	Vs3	Vs3	Vs3
4	GND	SM2	SM3	GND	-12V_Aux	GND	SYSRESET*	NVMRO	GND
5	GND	GAP*	GA4*	GND	3.3V_Aux	GND	SM0	SM1	GND
6	GND	GA3*	GA2*	GND	+12V_Aux	GND	GA1*	GA0*	GND
7	TCK	GND	GND	TDO	TDI	GND	GND	TMS	TRST*
8	GND	REF_CLK-	REF_CLK+	GND	GND	AUX_CLK-	AUX_CLK+	GND	GND

VS1=12V , VS2=3.3V , VS3=5V

Pin Assignment P1 & J1

Backplane J2	Row i	Row h	Row g	Row f	Row e	Row d	Row c	Row b	Row a
1	SEwafer1	GND	GND-J2	LN0-TD-	LN0-TD+	GND	GND-J2	LN0-RD-	LN0-RD+
2	GND	LN1-TD-	LN1-TD+	GND-J2	GND	LN1-RD-	LN1-RD+	GND-J2	GND
3	SEwafer3	GND	GND-J2	LN2-TD-	LN2-TD+	GND	GND-J2	LN2-RD-	LN2-RD+
4	GND	LN3-TD-	LN3-TD+	GND-J2	GND	LN3-RD-	LN3-RD+	GND-J2	GND
5	SEwafer5	GND	GND-J2	LN4-TD-	LN4-TD+	GND	GND-J2	LN4-RD-	LN4-RD+
6	GND	LN5-TD-	LN5-TD+	GND-J2	GND	LN5-RD-	LN5-RD+	GND-J2	GND
7	SEwafer7	GND	GND-J2	LN6-TD-	LN6-TD+	GND	GND-J2	LN6-RD-	LN6-RD+
8	GND	LN7-TD-	LN7-TD+	GND-J2	GND	LN7-RD-	LN7-RD+	GND-J2	GND
9	SEwafer9	GND	GND-J2	LN8-TD-	LN8-TD+	GND	GND-J2	LN8-RD-	LN8-RD+
10	GND	LN9-TD-	LN9-TD+	GND-J2	GND	LN9-RD-	LN9-RD+	GND-J2	GND
11	SEwafer11	GND	GND-J2	LN10-TD-	LN10-TD+	GND	GND-J2	LN10-RD-	LN10-RD+
12	GND	LN11-TD-	LN11-TD+	GND-J2	GND	LN11-RD-	LN11-RD+	GND-J2	GND
13	SEwafer13	GND	GND-J2	LN12-TD-	LN12-TD+	GND	GND-J2	LN12-RD-	LN12-RD+
14	GND	LN13-TD-	LN13-TD+	GND-J2	GND	LN13-RD-	LN13-RD+	GND-J2	GND
15	SEwafer15	GND	GND-J2	LN14-TD-	LN14-TD+	GND	GND-J2	LN14-RD-	LN14-RD+
16	GND	LN15-TD-	LN15-TD+	GND-J2	GND	LN15-RD-	LN15-RD+	GND-J2	GND

3U VPX Power & GND
2 Slot BACKPLANE
J1 Differential, J2 Universal

VITA 46
VITA 65



Pin Assignment P2 & J2



This connector is all User Defined pins. See Section 6.3.3 for requirements and pin assignments concerning connectors that are all User Defined.

Backplane Jn	Row i	Row h	Row g	Row f	Row e	Row d	Row c	Row b	Row a
1	UD	UD	UD	UD	UD	GND	UD	UD	UD
2	GND	UD	UD	GND	UD	UD	UD	UD	GND
3	UD	UD	UD	UD	UD	GND	UD	UD	UD
4	GND	UD	UD	GND	UD	UD	UD	UD	GND
5	UD	UD	UD	UD	UD	GND	UD	UD	UD
6	GND	UD	UD	GND	UD	UD	UD	UD	GND
7	UD	UD	UD	UD	UD	GND	UD	UD	UD
8	GND	UD	UD	GND	UD	UD	UD	UD	GND
9	UD	UD	UD	UD	UD	GND	UD	UD	UD
10	GND	UD	UD	GND	UD	UD	UD	UD	GND
11	UD	UD	UD	UD	UD	GND	UD	UD	UD
12	GND	UD	UD	GND	UD	UD	UD	UD	GND
13	UD	UD	UD	UD	UD	GND	UD	UD	UD
14	GND	UD	UD	GND	UD	UD	UD	UD	GND
15	UD	UD	UD	UD	UD	GND	UD	UD	UD
16	GND	UD	UD	GND	UD	UD	UD	UD	GND

3) Current Capability:

▪ +12V	28 A
▪ +3.3V	28 A
▪ +5V	30 A
▪ -12V AUX	2 A
▪ +12V AUX	2 A
▪ +3.3V AUX	2 A

4) UTILITY (Connector XUTIL)




Connector FCI/Berg Art. Nr. 95615-014TRLF

3U VPX Power & GND 2 Slot BACKPLANE J1 Differential, J2 Universal	VITA 46 VITA 65	
--	----------------------------------	--

5) JTAG (Connector XJT1)



Consider: JTAG only at Slot 1



Connector J.S.T. BM06B-SRSS-TB(LF)(SN)

6) SYSCON


By setting the signal Syscon to GND the system slot is defined. In general the system slot is slot 1.

We offer 2 options for setting:

- Jumper (standard)
- 0 Ohm Resistor for rugged applications

X_SC12

1	SYSCON1
2	GND
3	SYSCON2



7) I2C Connector

There are 2 connectors for system-management I2CA and I2CB.

For customer specific board assembly Zero-Ohm resistors available.

Usable voltages for I2C are 3.3V-AUX

I2CA

1	I2CA_SCL
2	GND
3	I2CA_SDA
4	I2CA_PWR
5	NC

I2CB

1	I2CB_SCL
2	GND
3	I2CB_SDA
4	I2CB_PWR
5	NC

Connector Molex Art. Nr. 53398-0571

3U VPX Power & GND
2 Slot BACKPLANE
J1 Differential, J2 Universal



VITA 46
VITA 65



8) Power Connections M3 screws

The main operating voltages and GND are supplied with M3 screw.

The auxiliary operating voltages are supplied via 4-pole pin strip XAUX. Optimal daughter board supply and trouble-free operation are ensured by the arrangement of the feed modules on the backplane.




Connector Samtec
p/n TSM-104-01-L-SV

9) XBAT

Normally a battery voltage with approximately 3V is available at Pin VBAT of connector VPX-J1. The voltage is externally accessible with connector XBAT, Pin2 **or** internally using 3.3V_AUX by setting a Jumper between Pin2 and Pin3.

VBAT X5

1	GND
2	+VBAT
3	+3.3V_AUX




Connector Samtec Art. Nr. TSM-103-01-L-SV

10) NVMRO

If Jumper BR1 is closed NVRMO is set to memory writeable.

BR1

1	NVMRO
2	GND



Germany

Hartmann Electronic GmbH
Phone: +49 711 13 98 90
Fax: +49 711 8 66 11 91
vertrieb.he@kontron.com
www.hartmann-electronic.com

USA

Kontron
Fabian Hemmann
Phone: +1 937-324-2420
Mobile: +1 937 346 7878
fabian.hemmann@us.kontron.com
www.hartmann-electronic.com

France

Kontron Modular Computers S.A.S.
Serge Pichat
Phone: +33 (0)9 66 44 03 15
Mobile: +33 (0)6 82 62 16 00
Serge.pichat@kontron.com
www.hartmann-electronic.com

India

Hartmann Electronic GmbH
Vivek Deshpande
Phone: +1 91 20 66 74 51 23
Vivek.Deshpande@kontron.com
www.hartmann-electronic.com